

SIGHT FLOW INDICATORS

FITZER SIGHT FLOW INDICATORS ARE RECOMMENDED WHERE VISIBILITY IS OF UTMOST IMPORTANCE AND MAXIMUM VIEW IS DESIRED FOR LIQUID FLOW INDICATE IN VERTICAL OR HORIZONTAL PIPE LINE IN PROCESS PLANT OR DISTILLATION APPARATUS.



SFI / 804



SFI / 805

DOUBLE WINDOW TYPE : TECHNICAL SPECIFICATION

Size	: 15 to 300 NB
Body	: Fabricated in MS, S.S. 304, S.S. 316, S.S.316L OR Poly Propylene upto 50 NB)
Window	: Toughened Borosilicate glass
Gasket	: C.A.F. OR PTFE (optionally)
Op.Pressure	: 20 Kg / cm ² (upto 100 NB) 10 Kg / cm ² (upto 200 NB) 6 Kg / cm ² (above 200 NB)
Process Connection	: ANSI, BS10 OR DIN type

FULL VIEW TYPE : TECHNICAL SPECIFICATION

Size	: 15, 20, 25, 40 50, 80, 100, 150, NB
Body	: Fabricated in MS, S.S. 304, S.S. 316, S.S. 316L OR Poly Propylene upto 50 NB)
Glass Tube	: Buttressed Borosilicate Glass
Gasket	: C.A.F. OR PTFE (optionally)
Hyd. Pressure	: 10 Kg / cm ² (upto50NB) 6 Kg / cm ² (upto 100 NB) 4 Kg / cm ² (above 100 NB)
Process Connection	: ANSI, BS10 OR DIN type



MODEL NO.:FITZER / SFI / 804

Drip type :Recommended for downward vertical or horizontal flow.



MODEL NO.:FITZER / SFI / 801

Flapper type Sight flow indicators are best suited for horizontal flow OR vertically up ward flow The position of flapper gives an indication of the flow passing.



MODEL NO.:FITZER / SFI / 807

MOC:PTFE BUSHING TYPE



MODEL NO.:FITZER / SFI / 806

MOC:PTFE LINED TYPE

Also Available:

Sight Flow indicators with rotating wheel are recommended for dark liquid where flow is detected easily by motion of the rotating wheel. These indicators are suitable for any flow direction.